



Revised 10/06/2017

MINI Cooper Sway Bar Length Reference Chart

Factory MINI Sway Bar Link Lengths					MAXX-G ADJUSTABLE Link Kit PN	
	Front		Rear		Front	Rear
	inch	mm	inch	mm		
R50 R53	11.8	300	9.1	230	10-510600	10-510400
R55 R59	11.8	300	9.1	230	10-510600	10-510400
R60 R61	11.6	295	6.3	155	10-510600	10-510100
F55 F56	13.0	330	4.3	108	10-510700	

MINI Sway Bar Link Lengths					MAXX-G ADJUSTABLE Link Kit PN	
	Front		Rear		Front	Rear
	inch	mm	inch	mm		
R50 R53 (Standard Ride Height)	11.8	300	9.1	230	10-510600	10-510400
R50 R53 (lowered 1.5")	12.8	325	7.8	198	10-510700	10-510300
R50 R53 (1" Lift)	10.8	275	9.9	251	10-510500	10-510400
R50 R53 (2" Lift)	9.8	249	10.9	277	10-510400	10-510500
R55 R59 (Standard Ride Height)	11.8	298	9.1	230	10-510600	10-510400
R55 R59 (Lowered 1.5")	12.8	325	7.8	198	10-510700	10-510300
R55 R59 (1" Lift)	10.8	274	9.9	251	10-510500	10-510400
R55 R59 (2" Lift)	9.8	249	10.7	272	10-510400	10-510500
R60 R61 (Standard Ride Height)	11.6	295	6.3	160	10-510600	10-510100
R60 R61 (1.5" Lowered)	12.6	320	5.1	130	10-510700	10-510100
R60 R61 (2" Lift)	9.6	244	7.8	198	10-510400	10-510200
Gen 3 F54 & F60 (Standard Ride Height)	13.0	330	4.3	109	10-510700	10-515100
F54 F60 (1.5" Lowered)	14.5	368			10-510800	
F54 F60 (2" Lift)	11.0	279			10-510600	

Sway Bar Links - Adjustable Length Range		
MAXX-G Assembly PN	mm	inch
10-510100	150-175	5.9-6.9
10-510200	175-200	6.9-7.9
10-510300	200-225	7.9-8.9
10-510400	225-250	8.9-9.9
10-510500	250-275	9.9-10.9
10-510600	275-300	10.9-11.9
10-510700	300-325	11.9-12.9
10-510800	325-350	12.9-13.9